Axle Torque Specs Harley Davidson Forums

How to Build a Harley-Davidson Torque Monster 101 Harley-Davidson Performand Projects Donny’s Unauthorized Technical Guide to Harley-Davidson, 1936 to Present Donny's Unauthorized Technical Guide to Harley-Davidson, 1936 to Present Donny’S Unauthorized Technical Guide to Harley-Davidson, 1936 to Present 101 Harley-Davidson Twin Cam Performance Projects Donny’S Unauthorized Technical Guide to Harley-Davidson, 1936 to Present Harley-Davidson Sportster Performance Handbook, 3rd Edition 101 Harley-Davidson Evolution Performance Projects Ford F-150 Pickup 1997-2005 Donny’S Unauthorized Technical Guide to Harley-Davidson, 1936 to Present Harley-Davidson Big Twins Owners Workshop Manual Harley-Davidson Buyer's Guide Chilton's Harley-Davidson Repair and Tune-up Guide Original Harley-Davidson Knucklehead WALNECK'S CLASSIC CYCLE TRADER, DECEMBER 1998 Harley-Davidson All Military Vehicles of the United States (1952) WALNECK'S CLASSIC CYCLE TRADER, APRIL 2005 WALNECK'S CLASSIC CYCLE TRADER, DECEMBER 1988

Check Front Axle Nut Torque **Trick for Getting Torque Specs**

HD Ultra Classic Primary Removal and Installation**Check Front Axle Nut Torque How to Adjust Drive Belt Tension and Align the Axle on a Harley** How To Remove \u0026 Install Front Wheel - Harley Davidson Softail *Check Rear Axle Nut Torque*

Doc Harley: Lug Nut TorqueProper axle installation for harley davidson *Dyna Clutch basket pt 2*

How To Harley Davidson Wheel Remove And Install.

How To Remove \u0026 Install Rear Wheel - Harley Davidson SoftailHarley Davidson Street Glide rear wheel removal Shifter Linkage / Axle Nut Covers Upgrade Electra Glide Standard **Installing axle nut covers on a 2018+ Fat Bob - and a warning about the HD pivot bolt cover!** DOC HARLEY: REAR AXLE ADJUSTING How to use torque wrench for beginners *2016 Doc Harley: COMPENSATOR Remove Harley Bearings Without a Bearing Puller! Barnett Extra PLate Kit and H-D Diaghram Spring Installation* DOC HARLEY: TIRE CHANGING MISTAKES How to Remove a Front Motorcycle Tire **Stator Repair - 3d of 9 - Clutch Installation - Torq specs.AVI** *How To Harley Davidson Wheel Remove \u0026 install.* Delboy's Garage, Harley Davidson rear wheel alignment, made easy. **How to Replace a Clutch in a Big Twin Harley Davidson**

Factory to SE Compensator Swap: Part 2 - Reassembly 2014 HARLEY-DAVIDSON HEAD TORQUE SPECS ☐☐☐☐1200c hd how to set your torque specs front end *Harley Davidson Timken Wheel Bearing Install and end play check model years 1970-99 Grim Parts Co* Axle Torque Specs Harley Davidson

If you are unsure of the proper torque value to use, here is a general chart of fastener torque values. This table is based upon Grade 5 fasteners, generally used Harley-Davidson motorcycles. Fastener Size - Torque ft. lbs. #8 - 14 in. lbs. #10 - 22 in. lbs. 1/4 " - 10 ft. lbs. 5/16" - 19 ft. lbs. 3/8" - 33 ft. lbs.

Bolt Torque Values - Nightrider.com

This will pull the frame and exhaust bracket down & out of your way. Do whatever is necessary so that you can access the axle nut with a torque wrench and the large 36mm socket. To check the nut torque, use a 36 millimeter socket and set the torque wrench to 95 to 105 foot pounds. You do not need to remove the axle retaining clip.

Checking a Harley-Davidson's Rear Axle Nut Torque | Fix My Hog

The factory service manual lists the front axle torque spec as 70 to 75 foot pounds. We would always suggest reaching for the higher number on a larger fastener such as this. The front axle nut is metric. Use a twenty four millimeter socket with a reliable torque wrench.

Check Front Axle Nut Torque | Fix My Hog

Harley-Davidson motorcycles specifications, all models timeline. 2020 Zanella Patagonian Eagle 350 Chopper

Harley-Davidson Motorcycles Specs, Timeline

Torque the axle nut to 60 to 65 foot-pounds, using a foot-pound torque wrench and socket. If you're working on a Softail model, torque the slider cap nuts to 11 to 15 foot-pounds, and ensure that the gaps at the front and the rear of the sliders are equal. On a Dyna, torque the rear fastener to 10 to 14 foot-pounds, then torque the front fasteners to 10 to 14 foot-pounds.

How to Tighten the Front Axle on a Harley | It Still Runs

The factory service manual lists the front axle torque spec as 70 to 75 foot pounds. We would always suggest reaching for the higher number on a larger fastener such as this. The front axle nut is metric.

Torque Spec Harley - equitylasopa

Front Axle Cone Nut = 60-65 ft-lbs. Front Axel Holder Nuts = 132-180 in-lbs Can't remember the torque specs on the calipers bolts and not where I can verify that at the moment.

Torque specs for front wheel install?? | Road Glide

The torque on the rear axle is 95-105ft-lbs. Here's a few more torque values for the rear end i thought you might need or at least have for future reference if needed? Rear caliper banjo bolt 17-22 ft-lbs Brake caliper mounting bolt, rear 16-20 ft-lbs Brake disc screws, rear 30-45 ft-lbs Brake pad pin, rear caliper 80-120 in-lbs Brake caliper bleeder valve 80-100 in-lbs

What is the torque specifications for the rear axle on a ...

There is no torque specs,this nut has to be tightened back like it was ,the best thing to do,was,to late now,is to use a torque wrench to remove the nut,and remember the torque,and when replacing it,torque it back to that spec,the reason being,there is a crush sleeve between the front pion bearing ,and the rear pinion bearing,and it has to be crushed to a certain amount,to aquire deepness into the ring gear,anyway just give it about 25 lbs torque,any more the crush sleeve will crush even ...

SOLVED: Rear axle torque specs for 2014 Harley Davidson ...

if your talking about the axel cap fastener--torque is 132-180 INCH-LBS, tighten front first then rear. if done properly there should be no gap in the front 1 - 4 of 4 Posts

2010 wide glide torque spec | V-Twin Forum

An expert that got 5 achievements. Harley Davidson Master. 3,506 Answers. Re: NNeed torque specs for 2010 harley ultara classic,... Front Axle = 60 to 65 foot pounds. Front caliper banjo bolts = 17 to 19 foot pounds. Front Brake disk screws = 16 to 29 foot pounds. Front caliper mounting bolts = 28 to 38 foot pounds.

SOLVED: NNeed torque specs for 2010 harley ultara classic ...

The earlier model softy's were 60-65 ft lb but at some point "probably 07" they went with a heavier axle and larger 36 ml nut. The torque for these bikes is 95-105 ft lbs as HugoBetz said earlier. 1 - 6 of 6 Posts

09 softail rear axle nut torque | V-Twin Forum

On models with dual front calipers, check alignment of brake discs to fork. Loosen slider cap nuts and axle nut. Insert a 7/16 in drill bit (1) through hole in front axle. Contact point (2) must have edge of drill touching the edge of fork leg. Tighten front axle to proper torque. Refer to applicable Service Manual.

Harley-Davidson

Hi, I have a 2008 Harley Davidson sportster and would like to know if it is okay to reverse the rear wheel axle to stop having to remove the rear muffler when removing the rear wheel. Are thee any iss ...

What is the torque spec for the rear axle on a 1992 FLHS ...

Harley's head-bolt torque method harkens back to a time when torque specifications were less scientific. Minton explains that the procedure requires the use of a torque wrench but not for final tightening. First, you should pre-load the bolts to about 16 foot-pounds. Then, with a pencil, make a witness mark on both the cylinder head and head bolt.

Copyright code : 256a689711f49e40f9d301de0c1ba61a